



US009410658B2

(12) **United States Patent**
Runger

(10) **Patent No.:** **US 9,410,658 B2**
(45) **Date of Patent:** **Aug. 9, 2016**

(54) **PROJECTOR ADJUSTMENT MECHANISM**

USPC 248/274.1, 286.1, 287.1, 317, 320, 323,
248/324, 337, 340, 342, 343, 344, 346.06,
248/371, 519, 327; 362/259, 253, 243, 242
See application file for complete search history.

(71) Applicant: **Ergotron, Inc.**, St. Paul, MN (US)

(72) Inventor: **George Runger**, Eagan, MN (US)

(73) Assignee: **Ergotron, Inc.**, St. Paul, MN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **14/477,158**

(22) Filed: **Sep. 4, 2014**

(65) **Prior Publication Data**

US 2015/0060625 A1 Mar. 5, 2015

Related U.S. Application Data

(60) Provisional application No. 61/874,037, filed on Sep. 5, 2013.

(51) **Int. Cl.**

A47B 96/00 (2006.01)
A47K 1/00 (2006.01)
A47K 5/00 (2006.01)
F21V 21/00 (2006.01)
F21V 35/00 (2006.01)
F16L 3/08 (2006.01)
F16M 11/04 (2006.01)

(Continued)

(52) **U.S. Cl.**

CPC **F16M 11/043** (2013.01); **F16M 11/08** (2013.01); **F16M 11/12** (2013.01); **F16M 13/02** (2013.01); **F16M 13/022** (2013.01); **F16M 13/027** (2013.01); **G03B 21/145** (2013.01); **G03B 21/54** (2013.01)

(58) **Field of Classification Search**

CPC F16M 11/12; F16M 11/18; F16M 13/02; F16M 11/2092; F16M 11/04; F16M 11/043; F16M 11/2035; F16M 11/123; G03B 21/54; G03B 21/145

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,643,844 A 6/1953 Nette
3,516,628 A 6/1970 Kendall

(Continued)

FOREIGN PATENT DOCUMENTS

CN 202228878 U 5/2012
CN 202327583 U 7/2012

(Continued)

OTHER PUBLICATIONS

"International Application Serial No. PCT/US2014/025624, International Search Report mailed Aug. 22, 2014", 5 pgs.

(Continued)

Primary Examiner — Jonathan Liu

Assistant Examiner — Muhammad Ijaz

(74) *Attorney, Agent, or Firm* — Schwegman Lundberg & Woessner, P.A.

(57) **ABSTRACT**

In one example, a device for mounting and adjusting an electronic device is described. The device can include a mounting frame, an elongated shaft connected to the mounting frame, a curved arm for operatively connecting to an electronic device and slidably engaging with the shaft, and a threaded knob configured for threadable engagement with the curved arm.

13 Claims, 3 Drawing Sheets

